



# SPE blocking element incl. surface mounting kit



The blocking element incl. kit is for installation on the frame or on the door.

A conventional magnetic contact can be used in the kit:

- EMK 46 Z flush-mount magnetic contact for VdS Class B
- MK 48 SZ flush-mount magnetic contact for VdS Class C

## Certifications and Approvals

Region	Certification
Europe	CE Sperrelement SPE

## Technical Specifications

SPE blocking element

Bolts max. distance to locking plate	4 mm
Break force for emergency open	0.8 to 1 kN
Cable to control unit	Max. 6 m, 6-pin, shielded, permanently cast
Environmental conditions	
• Protection category	IP 44
• Operating temperature	-25 °C to +55 °C
• Storage temperature	-40 °C to +85 °C
Housing	
• Material	ABS
• Color	RAL 9002
Dimensions (H x W x D)	28 x 118 x 16 mm
Weight	0.45 kg

## Ordering Information

<b>SPE blocking element incl. surface mounting kit</b>	<b>4998013609C20;4</b>
For installation on frame/door	<b>998149110</b>

**Americas:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Bosch Security Systems Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3450  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**