

AXIS P1427-E Network Camera

Compact and cost-effective 5 megapixel surveillance

The AXIS P1427-E bullet camera provides excellent image quality in 5 megapixel resolution. The camera features a vari-focal P-iris lens. P-iris control provides optimal depth of field, resolution, image contrast and clarity. AXIS P1427-E supports Axis' Corridor Format for vertically oriented video streams. The pixel counter assures that the pixel resolution of an object fulfills requirements for identification purposes. Remote zoom and focus eliminate the need for hands-on fine tuning. The input/output port can be used for notification to an alarm panel or control of a relay. The outdoor-ready camera has an adjustable weather shield protecting it from rain, snow and direct sunlight.

- > **5 megapixel resolution at 12 fps**
- > **Day & Night functionality**
- > **Edge storage**
- > **Ease of installation**
- > **I/O support**



AXIS P1427-E Network Camera

Camera		
Image sensor	Progressive scan CMOS 1/3.2"	
Lens	2.8–9.8 mm, F1.6 Horizontal field of view 27° – 92° Varifocal, Autofocus, Remote focus and zoom, P-Iris control, IR corrected	Notification: email, HTTP, HTTPS and TCP and SNMP trap External output activation Video recording to edge storage Pre- and post-alarm video buffering PTZ preset, Overlay text
Day and night	Automatically removable infrared-cut filter	Built-in installation aids
Minimum illumination	Color: 0.35 lux at F1.6 B/W: 0.07 lux at F1.6	Pixel counter, Remote zoom (3–3.5x optical), Remote focus
Shutter time	1/28000 s to 2 s with power line frequency 50 Hz 1/33500 s to 2 s with power line frequency 60 Hz	Data streaming
Video		Event data
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	General
Resolutions	2592x1944 HDTV 1080p to 160x90 Meets relevant parts of SMPTE 274M (HDTV 1080p)	Casing
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions Resolutions up to 1920x1080 (HDTV 1080p) and 1600x1200: Up to 25/30 fps (50/60 Hz) 3 MP capture mode: Up to 16/20 fps (50/60 Hz) 5 MP capture mode: Up to 12,5/12 fps (50/60 Hz)	Sustainability
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/MBR H.264	PVC free
Image settings	Manual shutter time, Compression, Color, Brightness, Sharpness, White balance, Exposure control, Exposure zones, Fine tuning of behavior at low light, Text and image overlay, Privacy masks Wide Dynamic Range – Dynamic Contrast Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Memory
Pan/Tilt/Zoom	Digital PTZ	512 MB RAM, 128 MB Flash
Network		Power
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 12.8 W
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Connectors
System integration		RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin terminal block for 1 alarm input and 1 output
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profiles S and G, specifications at www.onvif.org	Storage
Analytics	AXIS Video Motion Detection 3 Support for AXIS Camera Application Platform enabling installation of AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Event triggers	Analytics Detectors: Day/Night Mode, Live Stream Accessed Tampering Hardware: Network, Temperature Input Signal: Manual Trigger, Virtual Inputs Storage: Disruption, Recording System: System Ready Time: Use Schedule, Recurrences	Operating conditions
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email	-30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–100% RH (condensing)
		Storage conditions
		-40 °C to 65 °C (-40 °F to 149 °F)
		Approvals
		EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, IEC/EN 60529 IP66, NEMA 250 type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-27 EN 55022 Class A
		Weight
		With weather shield: 862 g (1.90 lb)
		Dimensions
		Ø132 x 260 mm (Ø5 3/16 x 10 1/4 in)
		Included accessories
		Mounting bracket, Drill template, Installation Guide, Windows decoder 1-user license AXIS Weather Shield L
		Optional accessories
		AXIS T94F01M J-Box/Gang Box Plate AXIS T91A47 Pole Mount AXIS T94P01B Corner Bracket AXIS T94F01P Conduit Back Box Axis PoE Midspans For more accessories, see www.axis.com
		Video management software
		AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
		Languages
		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		Warranty
		Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

www.axis.com/environmental-responsibility