

AXIS M5055 PTZ Network Camera

Mini PTZ with HDTV 1080p resolution

AXIS M5055 PTZ Network Camera is an ultra-discreet, palm-sized, pan-tilt-zoom camera for remote indoor monitoring. It provides full frame rate video in HDTV 1080p resolution, and supports multiple H.264 and Motion JPEG video streams. AXIS M5055 is a ceiling-mount camera that provides flexible coverage over a 500 m² (4300 sq. ft) area with $\pm 180^\circ$ pan, 90° tilt, and 5x optical zoom. The IP51 rating ensures protection against dust and dripping water, enabling the camera to operate even when a sprinkler system is activated.

- > **HDTV 1080p**
- > **5x optical zoom and autofocus**
- > **IP51-rated**
- > **Power over Ethernet (IEEE 802.3af)**
- > **Built-in analytics**



AXIS M5055 PTZ Network Camera

Camera		Storage: disruption, recording System: system ready Time: recurrence, use schedule
Image sensor	1/4.85" progressive scan RGB CMOS	
Lens	Varifocal. 2.2–11.0 mm, F1.4–F2.5 Horizontal field of view: 14°–71° Vertical field of view: 8°–40° Autofocus	Event actions Record video: SD card, network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS network share, email PTZ control: preset position Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text Status LED
Minimum illumination	Color: 1.2 lux at 30 IRE F1.4	
Shutter time	1/16000 s to 1 s	Data streaming Event data
Pan/Tilt/Zoom	Pan: ±179°, 100°/s Tilt: 90°, 100°/s Zoom: 5x optical, 10x digital 25 preset positions, control queue, on-screen directional indicator	Built-in installation aids Pixel counter
Video		General
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High profiles Motion JPEG	Casing IP51-rated plastic casing, clear dome
Resolution	1920x1080 to 320x180 (16:9)	Sustainability PVC free
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	Memory 512 MB RAM, 256 MB Flash
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Power Power over Ethernet 802.3af/802.3at Type 1 Class 3 Typical 4.6 W, max 7.8 W
Image settings	Resolution, compression, rotation: 0°, 180°, text and image overlay, color, brightness, sharpness, white balance, wide dynamic range, exposure control, exposure time, gain, exposure zones, exposure priority, image freeze on PTZ, privacy masks	Connectors RJ45 10BASE-T/100BASE-TX PoE
Audio		Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Audio streaming	One-way	Operating conditions 0 °C to 45 °C (32 °F to 113 °F) Humidity 10–90% RH (non-condensing)
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	Storage conditions -30 °C to 60 °C (-22 °F to 140 °F)
Audio input	Built-in microphone	Approvals EMC EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN-35 Safety IEC/EN/UL 62368-1 Environment IEC/EN 60529 IP51
Network		Dimensions Ø130 x 63 mm (Ø5.1 x 2.5 in)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management	Weight 375 g (0.8 lb)
Supported protocols	DIPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP ^a , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Included accessories Installation Guide, Windows decoder 1-user license
System integration		Optional accessories AXIS M50 Clear Dome Cover A AXIS M50 Mounting Kit For more accessories, see www.axis.com
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at onvif.org	Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms
Analytics	Included AXIS Video Motion Detection, AXIS Audio Volume detection, AXIS Scream Detection, AXIS Removed Object Detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Event triggers	Applications Detectors: live stream accessed Hardware: network Input signal: manual trigger, virtual inputs PTZ: moving, preset reached, ready	Warranty Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

www.axis.com/environmental-responsibility