

# NTL

## LARGE HOUSING FOR THERMAL CAMERAS

### MAIN FEATURES

Made of AISI 316L electropolished stainless steel

Germanium window

IP66/IP67

Available with different window dimensions: Ø 55mm (2.1in), Ø 70mm (2.8in) and Ø 110mm (4.3in)

Available accessories: heater, camera power supply

### DESCRIPTION

This housing for thermal camera provides the vision also in complete darkness, fog, rain, smoke or for long-range distances.

It is possible to use it for a wide range of high-security surveillance systems, such as: monitoring and rescue in the event of a fire, public safety, along with airport, industrial and environmental surveillance.

The germanium window is external non-scratch treated, Hard Carbon Coating (DLC), and internal antireflection; the spectral range is from 7.5 to 14µm.

The big dimensions of this camera housing make it suitable to contain the largest zoom lenses of the market.

The NTL housing can be installed on NXPTH Pan & Tilt head, to obtain a complete positioning system.



NTL + NXWBL



NTL + NXWBL

### AVAILABLE MODELS

| Model Number | Housing sunshield | Power supply 230Vac | Ø germanium window |
|--------------|-------------------|---------------------|--------------------|
| NTL1K1000    | ✓                 | ✓                   | 55mm (2.1in)       |
| NTL1K1300    | ✓                 | ✓                   | 70mm (2.8in)       |
| NTL1K1500    | ✓                 | ✓                   | 110mm (4.3in)      |

**TECHNICAL DATA**

**GENERAL**

Constructed from electropolished stainless steel (austenitic alloy stainless steel, corrosion and heat resistant according to the following standards):

AISI 316L

UNI 6900-71: X 2 Cr Ni Mo 17 12 2

DIN 17006: X 2 Cr Ni Mo 17 13 2

N° werkstoff 1.4404

AFNOR: Z2 CND 17-12

BSI: 316S11

The screws utilised are in austenitic alloy stainless steel, corrosion and heat resistant according to the following standards:

- UNI 6900: X 5 Cr Ni Mo 1712
- AISI: 316
- ISO quality: A4
- Resistance class ISO: 80

UNI: Ente Nazionale Italiano di Unificazione, AISI: American Iron and Standard Institute, DIN: Deutsche Industrie Normen, AFNOR: Association Française de Normalisation, BSI: British Standard Institution, ISO: International Organization for Standardization.

**MECHANICAL**

Cable glands: 4xPG13.5 (nickel-plated brass for external connections)

Flange thickness: 12mm (front), 9mm (back)

External body polishing

Gaskets: High sealing O-ring

Internal usable area (WxH): 112x112mm (4.4x4.4in)

Internal usable length: 562mm (22.1in)

Internal usable length (with heater): 477mm (18.7in)

Unit weight: 13kg / 28.7lb

Germanium window

- NTL1K1000 (internal) Dimensions (Ø): 70mm (2.8in) (external), 55mm (2.1in)
- NTL1K1300 (internal) Dimensions (Ø): 85mm (3.3in) (external), 70mm (2.8in)
- Thick: 2mm (0.07in)
- NTL1K1500 (internal) Dimensions (Ø): 125mm (4.9in) (external), 110mm (4.3in)
- Thick: 3mm (0.1in)
- External scratch-resistant treatment: Hard Carbon Coating (DLC)
- Internal antireflection treatment
- Spectral range: 7.5µm ÷ 14µm
- Medium transmittance (7.5µm ÷ 11.5µm): 94%
- Medium transmittance (11.5µm ÷ 14µm): 90%

**ELECTRICAL**

Heater (Ton 15°C±3°C (59°F±5°F), Toff 22°C±3°C (77°F±5°F))

- Power supply/Consumption: IN 12Vdc/24Vac, 20W max
- Power supply/Consumption: IN 120/230Vac, 40W max

**ENVIRONMENT**

Indoor/Outdoor

Operating temperature (with heater): -20°C (-4°F)/+60°C (140°F)

**CERTIFICATIONS**

Electrical safety (CE): EN60065

Electromagnetic compatibility (CE): EN50130-4, EN61000-6-3

IP protection degree: EN60529 (IP66/IP67)

EAC certification

**ACCESSORIES**

ONXLH1 Heater 120/230Vac

ONXLH2 Heater 12Vdc/24Vac

ONXPS1B Wide range power supply for camera IN 100-240Vac - OUT 12Vdc, 1A

ONXPS2B Camera power supply IN 230Vac - OUT 24Vac, 400mA

**BRACKETS AND ADAPTORS**

NXWBL Stainless steel wall bracket with joint

**RELATED PRODUCTS**






NXPHT Stainless steel P&T motor

**PACKAGE**




| Model Number | Weight        | Dimensions (WxHxL)              | Master carton |
|--------------|---------------|---------------------------------|---------------|
| NTL1K1000    | 15kg (33.5lb) | 29.5x35x75cm (11.6x13.8x29.5in) | -             |

**TECHNICAL DRAWINGS**

Sizes in millimeters.



FLANGIA FRONTALE



NTL

