

MANUFACTURED UNITS REFERENCE TABLES

Table A: Product Number Descriptions

Model #	Mbps	Fiber	Tx Wavelength (nm)	Rx Wavelength (nm)	Distance (km)	TX Power (dBm)	RX Sensitivity (dBm)	Loss Budget(dB m)	Fibers	Connector
SFP-1	10/100/1000	Copper	N/A	N/A	IEE802.3	N/A	N/A	N/A	N/A	RJ45
SFP-2	100	MM	1310	1310	2	-19	≤-30	11	2	LC
SFP-3	100	SM	1310	1310	20	-15	≤-31	16	2	LC
SFP-4	100	SM	1310	1310	40	-14	≤-34	20	2	LC
SFP-5	100	SM	1550	1550	80	-5	≤-31	26	2	LC
SFP-6	1000	SM	1310	1310	15	-8	≤-24	16	2	LC
SFP-7	1000	SM	1310	1310	40	-5	≤-24	19	2	LC
SFP-8	1000	SM	1550	1550	70	0	≤-24	24	2	LC
SFP-9	1000	SM	1550	1550	120	0	≤-32	32	2	LC
SFP-10A	100	SM	1310	1550	20	-14	≤-33	19	1	LC
SFP-10B	100	SM	1550	1310	20	-14	≤-33	19	1	LC
SFP-12A	1000	SM	1310	1550	20	-8	≤-22	14	1	LC
SFP-12B	1000	SM	1550	1310	20	-8	≤-22	14	1	LC
SFP-14A	1000	SM	1310	1550	20	-8	≤-22	14	1	SC
SFP-14B	1000	SM	1550	1310	20	-8	≤-22	14	1	SC
SFP-16	1000	MM	850	850	550m	-9.5	≤-17	7.5	2	LC
SFP-18A	1000	SM	1310	1550	60	-1	≤-26	25	1	LC
SFP-18B	1000	SM	1550	1310	60	-3	≤-26	23	1	LC
SFP-20A	100	SM	1310	1550	60	-5	≤-34	29	1	LC
SFP-20B	100	SM	1550	1310	60	-6	≤-34	28	1	LC
SFP-22A	1000	SM	1310	1550	60	-1	≤-26	25	1	SC
SFP-22B	1000	SM	1550	1310	60	-3	≤-26	23	1	SC
SFP-24A	100	SM	1310	1550	60	-5	≤-34	29	1	SC
SFP-24B	100	SM	1550	1310	60	-6	≤-34	28	1	SC
SFP-26A	100	MM	1310	1550	2	-15	≤-30	15	1	SC
SFP-26B	100	MM	1550	1310	2	-15	≤-30	15	1	SC
SFP-27	1000	SM	1310	1310	40	0	≤-24	24	2	LC
SFP-28	1000	SM	1510	1510	40	-5	≤-24	19	2	LC
SFP-29	1000	SM	1530	1530	40	-5	≤-24	19	2	LC
SFP-30	1000	SM	1550	1550	40	-5	≤-24	19	2	LC
SFP-31	1000	SM	1570	1570	40	-5	≤-24	19	2	LC
SFP-36A	100	SM	1310	1550	20	-15	≤-34	19	1	SC
SFP-36B	100	SM	1550	1310	20	-15	≤-34	19	1	SC
SFP-SX	1000	MM	850	850	550m	-9.5	≤-17	7.5	2	LC
SFP-LX/LH	1000	SM & MM	1310	1310	10/550m	-9.5	≤-20	10.5	2	LC
SFP-ZX	1000	SM	1550	1550	70	0	≤-23	23	2	LC
SFP-BXU	1000	SM	1310	1490	10	-9	≤-19.5	10.5	1	LC
SFP-BXD	1000	SM	1490	1310	10	-9	≤-19.5	10.5	1	LC

END OF SECTION