

## IQ8Alarm/Sp signaler with isolator, red, composed version



### Part-No. 807332.SV98

Approval: VdS

Same as 807322.SV98, but with an individual combination of up to 5 languages, see special order form in the appendix.

#### Features:

- Completely bus supplied alarm device
- Powered loop compatible
- Low power consumption
- Up to 32 alarm devices for each powered loop
- Each alarm device has built-in isolator
- Tones can be used for other purposes in addition to warning of fire, making the device ideal for use in schools etc.
- Soft start option, ideal for hospitals and nursing homes

#### Acoustic alarm signaling (dependent on type):

- Acoustic pressure up to 99 dB(A) @ 1 m
- Volume programmable in 8 steps via tools 8000
- Up to 26 different languages are available
- 20 different signaling tones, including DIN tone
- Multilingual speech alarm in 5 different languages
- Alarm signaling, evacuation, and test alarm can each be programmed in different languages
- Speech alarm, 5 pre-programmed alarm texts and other country-typical alarm signals

Operating voltage	8 ... 42 V DC (via powered loop)
Quiescent current @ 19 V DC	55 µA
Quiescent current @ FACP battery	approx. 300 µA @ 42 V
Sound level	97 dB (A) +/- 2 dB @ 1 m
Ambient temperature	-5 °C ... 50 °C
Storage temperature	-10 °C ... 55 °C
Type of protection	IP 30 (IP 65 with socket 806201 / 806202)
Housing	ABS plastic
Air humidity	< 95 %
Weight	approx. 300 g
Specification	EN 54-3 acoustic signaling device
Dimensions	Ø: 112 mm D: 75 mm Ø: 112 mm D: 90 mm (with IP 65 base)



When ordering, please note the "Ordering information for IQ8Quad and IQ8Alarm" and fill in "Order form for individual combination of languages?" printed in the appendix. Cancellations or returns are not possible.



Up to 5 different languages ? individually programmed ? are included.

#### Accessories:

806202 IP65 base, red