

## AXIS P1367-E Network Camera

Outdoor-ready 5 MP video in all light conditions

The 5 MP resolution at full frame rate ensures great video quality with a high level of details. The innovative outdoor-ready camera P1367-E is built for all weather conditions, with a quick and easy installation in mind. Built-in camera rails enable easier changing of lenses and with a simple roll of the sensor, the format shifts to Axis Corridor Format. In complex lighting or even in the dark, Forensic WDR together with Lightfinder will discover all details. Axis Zipstream technology optimizes the video stream saving bandwidth and storage while maintaining high video quality.

- > **5 MP resolution at 25/30 fps**
- > **Temperature range: -40 °C to 55 °C (-40 °F to 131 °F)**
- > **IK10-, IP66- and NEMA 4X-ratings**
- > **Lightfinder and Forensic WDR**
- > **Zipstream**



# AXIS P1367-E Network Camera

<b>Camera</b>		External output activation Video recording to edge storage, Play audio clip Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text Day/Night switching, Status LED activation Send SNMP trap
<b>Image sensor</b>	1/2.9" progressive scan RGB CMOS	
<b>Lens</b>	IR corrected, CS-mount lens, P-Iris Varifocal 2.8–8.5 mm, F1.2 <b>With IK10 protection in the front window:</b> Horizontal field of view: 72°–36° Vertical field of view: 40°–20° <b>Without IK10 protection in the front window:</b> Horizontal field of view: 83°–36° Vertical field of view: 45°–20°	
<b>Day and night</b>	Automatically removable infrared-cut filter	
<b>Minimum illumination</b>	Color: 0.15 lux B/W: 0.03 lux, at 50 IRE F1.2	
<b>Shutter time</b>	1/55500 s to 2 s	
<b>Video</b>		
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	
<b>Resolution</b>	3072x1728 (5 MP) to 160x90	
<b>Frame rate</b>	25/30 fps (50/60 Hz) in all resolutions	
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth	
<b>Multi-view streaming</b>	Up to 8 individually cropped out view areas	
<b>Image settings</b>	Saturation, contrast, brightness, sharpness, forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, text and image overlay, privacy masks	
<b>Pan/Tilt/Zoom</b>	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)	
<b>Audio</b>		
<b>Audio streaming</b>	Two-way, full duplex	
<b>Audio compression</b>	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 8/16/32/48 kHz Configurable bit rate	
<b>Audio input/output</b>	External microphone input or line input, line output	
<b>Network</b>		
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log	
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>™</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	
<b>System integration</b>		
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform, specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile G, specification at <a href="http://www.onvif.org">www.onvif.org</a>	
<b>Analytics</b>	AXIS Video Motion Detection 4, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>	
<b>Event triggers</b>	Analytics, open casing, edge storage events, external input, audio level, time scheduled	
<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP	
<b>Data streaming</b>	Event data	
<b>Built-in installation aids</b>	Focus assistant, pixel counter, remote back focus	
<b>General</b>		
<b>Casing</b>	IP66-, IP67- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure Color: White NCS S 1002-B	
<b>Sustainability</b>	PVC free	
<b>Memory</b>	1 GB RAM, 512 MB Flash	
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 9.2 W, typical 5.3 W	
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for two configurable inputs/outputs RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)	
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>	
<b>Operating conditions</b>	-40 °C to 55 °C (-40 °F to 131 °F) Maximum temperature (intermittent): 60 °C (140 °F) Humidity 10-100% RH (condensing)	
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)	
<b>Approvals</b>	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1 Environment EN 50121-4/IEC 62236, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK10 IEC/EN 60529 IP67	
<b>Dimensions</b>	382 x 155 x 120 mm (15 x 6.1 x 4.7 in)	
<b>Weight</b>	2.2 kg (4.9 lb)	
<b>Included accessories</b>	Installation Guide, Windows decoder 1-user license, wall mount bracket, sunshield, connector kit IK10 tool	
<b>Optional accessories</b>	Axis mounts, Axis lenses, Axis midspans For more accessories, see <a href="http://www.axis.com">www.axis.com</a>	
<b>Video management software</b>	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/support/downloads">www.axis.com/support/downloads</a>	
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

Environmental responsibility:  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)