



The performance features at a glance

- Energie saving LED Technology
- 32" screen size
- Max Resolution 1920 x 1080
- Aspect ratio 16:9
- VESA 200mm x 100mm and 200mm x 200mm
- HDMI (2), BNC, VGA inputs
- Integrated speakers

High versatility

Compact and yet large: the LME32 impresses with its very balanced image quality. Thanks to the 16:9 aspect ratio this one is especially suited for the recorder of the Pixelmaster (GXi) series and the Digimaster FX.

Outstanding advantages

Numerous inputs allow you to connect various devices to these monitors. Besides two HDMI slots, you also have a VGA and a BNC slot available.

Furthermore, you can feed in audio signals via PC Stereo or RCA (cinch) and make them audible via the integrated loud speakers.

High-performance technology

The maximum resolution is 1920 x 1080 with an aspect ratio of 16:9. A strong luminosity of 400cd/sq m produces clear images even in a bright environment.

Additional special features

Functions such as PIP or POP ensure greater transparency. Included are a HDMI cable and a power cord plus a remote control. A stand is already installed.

Order data

Order number	Product description
LME32	LED TFT, 32", max. 1920x1080 @60Hz, 8.5ms, image format 16:9, PAL/NTSC, built-in loudspeakers, VESA 200mm x 100mm / 200mmx200mm, with HDMI cable, remote control, power cord, stand

LME32 LED-Monitor




Advantages for the installer

Compact dimensions, low weight, and a clear OSD menu provide for simple commissioning. Furthermore, the LME32 is equipped with a VESA connection.

Accessoires

Order number	Product description
LMA-UWM100	Wall Mount VESA 200x200, 300x200, 400x100, 400x200, up to 100kg



Technical specifications	LME32
Video standard	PAL / NTSC
Screen size	32"
Resolution	1920 x 1080
Aspect ratio	16:9
Displayable colours	16,7 Million
Response time	8.5 ms
Angle of view (L/R)	88° / 88°
Luminosity	400 cd/m ²
Contrast range	5000 : 1
Operating hours (MTBF)	2x HDMI, BNC, VGA
Video inputs	BNC
Video outputs	PC Stereo, RCA
Audio inputs	RCA
Loudspeaker output	2x 1,5 Watt
OSD Menu	English, German, French, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech
3D Comb Filter / De-Interlace	Yes / Yes
PIP / POP	Yes / Yes
VESA connection	200mm x 100mm / 200mm x 200mm
Voltage supply	AC 100-240V 50/60HZ
Voltage supply Power consumption	70 Watt
Operating temperature	0°C - 40°C
Dimensions	747mm x 450mm x 80mm
Weight	12.1 kg
Housing	Metal
Accessories (incl)	HDMI cable, remote control, power cord